

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

easy clean sp

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Coating agent

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company

n-tec GmbH
Siemensstraße 13
84051 Essenbach - Altheim / GERMANY
Phone +49 - (0)87 03 - 98 97-64
Fax +49 - (0)87 03 - 98 97-65
Homepage www.n-tec.de
E-mail info@n-tec.de

Address enquiries to

Technical information

info@n-tec.de

Safety Data Sheet

sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body

+49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Flam. Liq. 2: H225 Highly flammable liquid and vapour.
Eye Irrit. 2: H319 Causes serious eye irritation.
STOT SE 3: H336 May cause drowsiness or dizziness.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms



Signal word

DANGER

Contains:


Propan-2-ol

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P280 Wear protective gloves / eye protection.
P271 Use only outdoors or in a well-ventilated area.
P405 Store locked up.
P312 Call a POISON CENTER / doctor if you feel unwell.
P501 Dispose of contents/container in accordance with local/national regulation.



2.3 Other hazards

Human health dangers	Frequent persistent contact with the skin can cause skin irritation.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

The product is a mixture.

Range [%]	Substance
80 - < 100	Propan-2-ol
	CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0, Reg-No.: 01-2119457558-25-XXXX
	GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336

Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Remove person to fresh air and keep comfortable for breathing. In the event of symptoms seek medical treatment.
Skin contact	In case of contact with skin wash off immediately with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse out mouth and give plenty of water to drink. Do not induce vomiting. Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Drowsiness
Vertigo
Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.


SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Carbon dioxide. Water spray jet. Dry powder. Alcohol-resistant foam.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.



5.3 Advice for firefighters

Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.
Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
Ensure adequate ventilation.
Use personal protective equipment (protective gloves, safety glasses, protective clothing).

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, universal absorbent, diatomaceous earth).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling


Provide suitable vacuuming at the processing machines and in the processing area.
Use only in well-ventilated areas.
Use solvent-resistant equipment.
Ignitable mixtures can be formed in the empty container.
Keep away from all sources of ignition - Refrain from smoking.
Take precautionary measures against static discharges.
Vapours can form an explosive mixture with air.
Use explosion-proofed equipment/fittings and non-sparking tools.
Do not eat, drink, smoke or take drugs at work.
After worktime and before work breaks the affected skin areas must be thoroughly cleaned.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.
Cloths contaminated with product should not be kept in trouser pockets.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Keep only in original container.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Do not store together with food and animal food/diet.
Keep container tightly closed.
Keep container in a well-ventilated place.
Keep in a cool place. Store in a dry place.
Protect from heat/overheating.
Keep locked up, out of reach of children.

7.3 Specific end use(s)

See product use, SECTION 1.2



SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Propan-2-ol
CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0, Reg-No.: 01-2119457558-25-XXXX
Long-term exposure: 400 ppm, 999 mg/m ³
Short-term exposure (15-minute): 500 ppm, 1250 mg/m ³

DNEL


Substance
Propan-2-ol, CAS: 67-63-0
Industrial, dermal, Long-term - systemic effects, 888 mg/kg bw/day
Industrial, inhalative (vapor), Long-term - systemic effects, 500 mg/m ³
general population, oral, Long-term - systemic effects, 26 mg/kg
general population, dermal, Long-term - systemic effects, 319 mg/kg bw/day
general population, inhalative (vapor), Long-term - systemic effects, 89 mg/m ³

PNEC

Substance
Propan-2-ol, CAS: 67-63-0
oral (food), 160 mg/kg food
sewage treatment plants (STP), 2251 mg/l
soil, 28 mg/kg
sediment (seawater), 552 mg/kg
sediment (freshwater), 552 mg/kg
seawater, 140,9 mg/l
freshwater, 140,9 mg/l

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	0,7 mm; Butyl rubber, >480 min (EN 374-1/-2/-3). The details concerned are recommendations. Please contact the glove supplier for further information.
Skin protection	Protective clothing (EN 340)
Other	Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Multi-purpose filter ABEK. (DIN EN 14387)
Thermal hazards	none
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	clear
Odor	alcoholic
Odour threshold	not applicable
pH-value	not applicable
pH-value [1%]	not determined
Boiling point [°C]	82
Flash point [°C]	13
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	2 Vol.% (Propan-2-ol)
Upper explosion limit	12 Vol.% (Propan-2-ol)
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	4,2 (20°C)
Density [g/ml]	0,79 (20 °C / 68,0 °F)
Bulk density [kg/m ³]	not applicable
Solubility in water	miscible
Solubility other solvents	No information available.
Partition coefficient [n-octanol/water]	not determined
Kinematic viscosity	not applicable
Relative vapour density	ca. 2,07
Evaporation speed	not determined
Melting point [°C]	-89
Auto-ignition temperature	425
Decomposition temperature [°C]	not determined
Particle characteristics	not applicable

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

The product is stable under standard conditions.

10.3 Possibility of hazardous reactions

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

Reactions with strong oxidizing agents.


Uncleaned empty vessels may contain product gases which can form explosive mixtures with air.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Oxidizing agent



Safety Data Sheet REACH(UK) (GB)
easy clean sp

n-tec GmbH
84051 Essenbach - Altheim




Date printed 06.04.2021, Revision 06.04.2021

Version 05. Supersedes version: 04

Page 6 / 12

10.6 Hazardous decomposition products

No hazardous decomposition products known.



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

Product
ATE-mix, oral, > 5000 mg/kg
Substance
Propan-2-ol, CAS: 67-63-0
LD50, oral, Rat, 4570 mg/kg

Acute dermal toxicity

Product
ATE-mix, dermal, > 5000 mg/kg
Substance
Propan-2-ol, CAS: 67-63-0
LD50, dermal, Rabbit, 13400 mg/kg

Acute inhalational toxicity

Product
ATE-mix, inhalation (vapour), > 20 mg/l 4h
Substance
Propan-2-ol, CAS: 67-63-0
LC50, inhalative, Rat, 30 mg/l/4h

Serious eye damage/irritation

Irritant
Based on the available information, the classification criteria are fulfilled.
Calculation method

Substance
Propan-2-ol, CAS: 67-63-0
Eye, Rabbit, Study, irritant

Skin corrosion/irritation

Based on the available information, the classification criteria are not fulfilled.

Substance
Propan-2-ol, CAS: 67-63-0
dermal, Rabbit, non-irritating

Respiratory or skin sensitisation

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity — single exposure


Vapours may cause drowsiness and dizziness.
Based on the available information, the classification criteria are fulfilled.
Calculation method

Substance
Propan-2-ol, CAS: 67-63-0
NOAEL, oral, Rat, 700 mg/kg bw/day, OECD 426, positive

Specific target organ toxicity — repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Substance



Propan-2-ol, CAS: 67-63-0

NOAEC, inhalative, Rat, 12500 mg/m³, OECD 451, negativ

Mutagenicity Based on the available information, the classification criteria are not fulfilled.

Reproduction toxicity Based on the available information, the classification criteria are not fulfilled.

Substance

Propan-2-ol, CAS: 67-63-0

NOAEL, oral, Rat, 853 mg/kg bw/day, OECD 415, negativ

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

Substance

Propan-2-ol, CAS: 67-63-0

NOAEC, inhalative, Rat, 12290 mg/m³, OECD 451, negativ

Aspiration hazard Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

Substance

Propan-2-ol, CAS: 67-63-0

EC50, (72h), Scenedesmus subspicatus, > 1000 mg/l

12.2 Persistence and degradability

Behaviour in environment compartments No information available.

Behaviour in sewage plant No information available.

Biological degradability No information available.

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment


Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

Do not discharge product unmonitored into the environment or into the drainage.
Ecological data of complete product are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Disposal in an incineration plant in accordance with the regulations of the local authorities.
For recycling, consult manufacturer.

Waste no. (recommended) 070604*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110* packaging containing residues of or contaminated by hazardous substances
150102


SECTION 14: Transport information**14.1 UN number**

Transport by land according to ADR/RID 1219

Inland navigation (ADN) 1219

Marine transport in accordance with IMDG 1219


Air transport in accordance with IATA 1219



14.2 UN proper shipping name

Transport by land according to ADR/RID Isopropanol, solution

- Classification Code F1


- Label 

- ADR LQ 1 l

- ADR 1.1.3.6 (8.6) Transport category (tunnel restriction code) 2 (D/E)


Inland navigation (ADN) Isopropanol, solution

- Classification Code F1

- Label 


Marine transport in accordance with IMDG Isopropanol solution

- EMS F-E, S-D

- Label 

- IMDG LQ 1 l

Air transport in accordance with IATA Isopropanol solution

- Label 

14.3 Transport hazard class(es)

Transport by land according to ADR/RID 3

Inland navigation (ADN) 3

Marine transport in accordance with IMDG 3

Air transport in accordance with IATA 3


14.4 Packing group

Transport by land according to ADR/RID II

Inland navigation (ADN) II

Marine transport in accordance with IMDG II

Air transport in accordance with IATA II



14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	2008/98/EC 2000/532/EC; 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006 (REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2021)
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people	Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.
- VOC (2010/75/CE)	> 85%


15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Hazard statements (SECTION 3)

H336 May cause drowsiness or dizziness.
H319 Causes serious eye irritation.
H225 Highly flammable liquid and vapour.



16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
EL50 = Median effective loading
ELINCS = European List of Notified Chemical Substances
EmS = Emergency Schedules
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
IVIS = In vitro irritation score
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
LL50 = Median lethal loading
LQ = Limited Quantities
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV@TWA = Threshold limit value – time-weighted average
TLV@STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Flam. Liq. 2: H225 Highly flammable liquid and vapour. (On basis of test data)
Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)
STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)

Modified position

SECTION 12 been added: Ecological data of complete product are not available.



Copyright: Chemiebüro®

